



28' LAUNDRY TRAILER

Our 28' Mobile Laundry Trailer supports basecamp operations with on-site fluff and fold laundry services, utilizing nine separate onboard washers and dryers. Supported by multiple tankless water heaters, the trailer's equipment delivers advanced wash cycle and temperature control options, and numerous dry options, alongside a laundry sink and on-board drying racks to facilitate laundry services rapidly and professionally, virtually anywhere.

see back for specifications





SPECIFICATIONS

Service Equipment:

- (8) Stackable washers & dryers; General Electric; #GUD37; 4.0 Cu. Ft. (IEC) Washers & 5.9 Cu. Ft. Electric Dryers
- (1) Oversized Top Load Washer; General Electric; GTW680BMKDG; 5.3 (IEC) Cu. Ft. Stainless Steel Capacity Washer
- (1) Oversized Electric Dryer; General Electric; GTD65EBMK0DG; GE 7.4 Cu. Ft. Capacity Duradrum2 Electric Dryer w/ Sensor Dry

Support Equipment:

- (3) Propane Tankless, On-Demand Water Heaters – A.O. Smith #JWT110P
- John Wood Tankless – 4RN5-W8HR-H968
- Operating Range/ each: 19,500-140,000 BTU/h
- Propane Inlet Pressure: 8.0" WC (min)/ - 14" WC (max)
- Electric: AC 120 volts 60 Hz
- Water Pressure: 15-150 PSI (above 40 recommended for max flow)
- Provides Endless How Water, on demand
- Compact, space-saving and energy conservation design
- (1) Laundry Sink w/ hot and cold water taps
- (2) 6-Foot Folding Tables
- (1) 8-foot shelf
- (3) 4-foot Wire rack shelving

HVAC:

- AC1501W AC Unit - Atwood AirCommand Rooftop AC & Heater
- 15,000 BTU/hr.; Nominal Cooling/ Heating Capacity
- 115v/ 60 Hz; Electric Rating
- 5,000 watt; Furnace/ Heat Pump

Electrical & Plumbing:

- (12) Additional 120V electric outlets

Fire Suppression:

- (1) ABC Extinguisher

Tandem Trailer Dimensions:

- 28'- Length
- 9' 4" - Vehicle Height/ Clearance
- 8' 6" - Width
- 7' 6" - Interior Height
- 16" - Deck Height

Trailer Specifications:

- Tandem 5200# axles trailer
- Electric front jack & (4) corner scissor jacks
- Ramp door at rear & 78" man door with window
- Moisture & mildew resistant DuraMax™ floors
- White Aluminum walls & ceiling; vinyl flooring
- LED lighting package; 4" vapor proof

Connection Requirements:

- Towing: 2-5/16" EZ Lock Ball Coupler
- Fresh Water: ¾ inch city water line to washing machines or tankless water heaters
- Grey Water: Uses 2 inch PVC disposal line from washing machines
- Propane: ¾" NPT to (2) front-mounted 100-lb tanks w/ cross over valve - TW 69.0; 108L; 31.3Kg
- Electric: 3-phase, 208 volts, 300 amps